



# SD -15-DC S p o t T y p e Water Leakage Detector

## Product Description

- Compact design, user friendly & easy installation.
- Robust & waterproof. All circuitries and electronic components are embedded inside epoxy resin.
- Long service life and low heat dissipation.
- Practically no maintenance is needed.
- High voltage and current rating of the relay dry contact output (NC/NO), can control electrical solenoid water valve directly.
- Normally closed / normally open relay dry contact output, multiple detectors can be connected in series / in parallel to reduce the number of Digital Input (DI) points needed in Building Management Systems (BMS).
- Relay energized when power is applied, green LED lights up. Blinking red LED indicates the detection of water.

## Technical Specifications

- Supply Voltage: 12-24V DC
- Maximum Current Consumption: 65mA
- Output: Relay Dry Contact (Normally Closed / Normally Open)
- Maximum Output Power Rating: 250V AC, 1A
- Response Time: Set to 5 seconds in order to eliminate false alarm
- Dimension: About 57 x 47 x 39mm (without the sensing probes)
- Weight: 125g
- Sensing Probes:
  - Package comes with a pair of "L" shape conductive electrode probes which can be setup into two different detection height levels by different orientation.
  - Can be replaced with most of the water sensing cables in the market.



**AQUTEK**® Asia Limited  
www.Aqutek.Asia